

Produktbereich Umweltsimulation

Fire and explosion hazard ATEX 137 1999/92/EG und ATEX 95 2014/34/EU

Danger assessment and determination of explosion protection zone for the test space as well as the installation site

	ATEX-Check list
Cust	omer:
Proj	ect/Order:
Com	piled by: Date: Signature:
<u>Gen</u>	neral conditions
1.	What kind of flammable substances is it all about?
	Substance:
	Flash point $^{1)}$:
	Ignition temperature:
	Safety data sheet available?
2.	Nature of testing
	testing product limits up to failure or destruction
	☐ long-term test at normal operation conditions for the product
	Please brief description of test, if possible with schematic diagram, on page 6 under any other business.
Test	t space
3.	What is the amount of flammable substances inside the test space? Text:

QM - Identifikation				Vom Nutzer auszufüllen	
FB 5194	Revision: 1	Erstellt am: 19.01.2017	Seite 1 von 6	Datei: FB5194_wut_en	Ersteller: J.Urban



4.	On what terms are flammable substances being introduced into the test space atmosphere? Please answer under 4.1 to 4.6 (4.1 to 4.4 to be available)
4.1	Under normal operation
	☐ applicable → the released amount is approx g (go on with 4.5)
	not applicable (go on with 4.2)
4.2	In case of an unpredictable fault due to cracking components
	applicable
	often can be excluded due to adequate component design
	the released amount is approx g high (lower explosion limit will be greatly exceeded) moderate (will be close to lower explosion limit) low (lower explosion limit certainly will not be exceeded) (go on with 4.5)
	not applicable (go on with 4.3)
4.3	By a leakage or destruction of specimen in the event of a predictable fault or during destruction test
	applicable
	due to leaks on gaskets or screw joints due to limit load as part of the test
	Prevalence often occasional uncommon
	Released amount often (lower explosion limit will be greatly exceeded) occasional (will be close to lower explosion limit) low (lower explosion limit certainly will not be exceeded) (go on with 4.5) not applicable (go on with 4.4)

QM - Identifikation				Vom Nutzer auszufüllen	
FB 5194	Revision: 1	Erstellt am: 19.01.2017	Seite 2 von 6	Datei: FB5194_wut_en	Ersteller: J.Urban



4.4	Due to diffusion out of specimen
	applicable -> diffusion rate g/h (go on with 4.5)
	not applicable (go on with 4.5)
4.5	At changing specimen
	applicable
	 the released amount is approx g very low (lower explosion limit certainly will not be exceeded) high (lower explosion limit will be greatly exceeded)
	not applicable
4.6	Are there flammable substances exposed inside the test space? (Possible only for storage below flash point and without pressure or at vaporisation rate below lower explosion limit)
	applicable
	not applicable
5.	Is the flammable substance under pressure?
	☐ applicable → bar overpressure
	permanent occasional
	not applicable
6.	At what temperatures is the test conducted? Text:

QM - Identifikation				Vom Nutzer auszufüllen	
FB 5194	Revision: 1	Erstellt am: 19.01.2017	Seite 3 von 6	Datei: FB5194_wut_en	Ersteller: J.Urban



7.	Does the specimen or specimen holder contain an own potential ignition source?
	\square applicable \rightarrow what kind of component is included?
	electronic components (ignition source due to a spark or a hot surface)own ignition source available during normal operationown ignition source only available in the event of a fault
	 mechanical components (ignition source due to a spark or a hot surface) own ignition source available during normal operation own ignition source only available in the event of a fault
	explosion protected acc. to Ex II _ G _ Category 1 _ or 2 _ or 3 _
	not applicable
8.	Classification into zones by the system user Test space classification based on information of point 1 to 7: ZONE 0 (chamber is not viable) permanent, long-term or frequent presence of an explosive atmosphere
	ZONE 1 occasional presence of an explosive atmosphere
	ZONE 2 usually an explosive atmosphere <u>does not exist</u> , <u>but however then only seldom and for a short period</u>
	None ZONE an explosive atmosphere does not exist. The design of the specimen and accordingly the specimen holder is safe enough so that flammable substances cannot escape as well an explosive atmosphere cannot arise during the test.

QM - Identifikation				Vom Nutzer auszufüllen	
FB 5194	Revision: 1	Erstellt am: 19.01.2017	Seite 4 von 6	Datei: FB5194_wut_en	Ersteller: J.Urban



_	_	
Inctal	lation	Cito
IIIStai	ıatıvı	JILE

9.	Is the specimen supplied with flammable substances by an external system? applicable not applicable
10.	Is the formation of explosive mixtures at the installation site expected? E. g. by adjacent supply systems
	☐ applicable → ZONE 2 (ZONE 0+1 not possible)☐ not applicable
11.	Where will the system be installed?
	in a special explosion-proved room ZONE 2 (installation not possible in ZONE 0 and 1)
	ZONE 2 up to 1m above the floor
	ZONE 2 in the entire room
	with the following protective measures: (text, respectively please brief description on page 6 under any other business)
	in a special protective room in which the creation of explosive zones is avoided by a
	sufficient aeration system (monitored and explosion-proved)
	in a normal laboratory with only limited access by application trained users
	in a normal laboratory with unrestricted access
	description of installation site: (text, respectively please brief description on page 6 under any other business)

QM - Identifikation				Vom Nutzer auszufüllen	
FB 5194	Revision: 1	Erstellt am: 19.01.2017	Seite 5 von 6	Datei: FB5194_wut_en	Ersteller: J.Urban



Produktbereich Umweltsimulation

Any other business

12. Description/schematic diagram/remarks